

HYPER•STRIKE



ADAPTING YOUR SIGHT FOR A LEFT-HANDED BOW

HYPER•STRIKE is packaged in a right-handed configuration, but with a few adjustments, the sight can be adapted for left-handed bows while maintaining all features and controls. In addition to the sight, you will need a set of standard hex wrenches to make the conversion.

1. Remove the windage lock screws. (Tool-less thumb screw on top, hex screw on bottom) Remove the mounting bracket. Flip the mounting bracket over, and replace. Reinstall the windage lock screws. Note: it is recommended to install the tool-less thumb screw on top (Side of mount with the TRUGLO logo) for easier access, but the sight will function either way.

2. The level will now appear to be upside down. A small hex head screw holds the level in place. Carefully remove this screw, making sure to retain the small square nut on the outside of the aperture. Reposition the level on the opposite side of the aperture, so the level is now inside the new "bottom" of the aperture. Using the hex screw and square nut, attach the level in the new position. (Do not over-tighten)

3. The sight is now configured for a left-handed bow, but the pins are in the incorrect order. (Increasing, instead of decreasing in diameter) The middle pin (Pin 3) can remain in the current position, but the other pins will need to be moved. Unscrew the TRU•LITE Pro rotary light, to make accessing the pins more comfortable.

4. Unscrew the hex screw on Pin 1 (Green, .019") and Pin 5 (Green, .010"). Be careful not to damage or kink the fiber-optics. Make sure to retain the square washer that fits into the track. Swap the positions of Pin 1 and Pin 5. (so Pin 1 is now at the top.) Loosely reattach the hex screws to hold the Pins 1 & 5 in place. Push Pins 1 & 5 to the outer ends of the track (top and bottom) to allow more room to access other pins.

5. Using the same method, switch Pin 2 (Amber, .019") and Pin 4 (Amber, .010"). Reattach pins, making sure the square washer is aligned in the track.

6. Move all pins towards the middle of the sight (towards Pin 3 that did not move) and tighten in place. Gently "pet" the fiber-optics on the back of the pins to push extra slack into the aperture. Be careful not to damage or kink the fiber. The new Pin order (From top to bottom) will be as follows:

- Pin 1, Green .019"
- Pin 2, Amber .019"
- Pin 3, Red .019"
- Pin 4, Amber .010"
- Pin 5, Green .010"

7. Replace the TRU•LITE Pro sight light. Follow standard installation and zeroing instructions.

TRUGLO[®]
WHEN BRIGHTNESS COUNTS™

For any further assistance, please call TRUGLO customer service at 1-888-887-8456 or email contactus@truglo.com